



# Matthews Paint Product Reference Guide: Conventional Satin

## Conventional Satin Intermix Colors 15-20° Gloss

N202SP White	N911SP Violet	N912SP Maroon	N913SP Magenta	N914SP Dark Red	N915SP Red Oxide	N917SP Yellow Oxide	N920SP Blue
N921SP Green	N923SP Black	N925SP New Blue	N929SP Carbon Black	N930SP Light Red	N940SP Red Yellow	N942SP Green Yellow	N947SP Scarlet Red

Because of variations in monitors and printers, the colors shown above may vary from the actual toner colors.

### Catalyst Options:

- **43270SP** for spray application
- **43999SP** for spray applications requiring a slower dry time
- **43621SP** for brush or roll applications. (Metallic paints are not recommended for brush or roll applications.)

### Reducer Options

- **6379SP** = Fast for cool weather applications not lower than 60-75°
- **45280SP** = Warm temp reducer for applications in temps between 70-80°
- **45290SP** = Hot weather applications with temps between 75-85°
- **6396SP** = Extreme Hot weather applications 85° and above
- **45251SP** = Retarder reducer must be used with 6396SP, to use this product; mix the 6396SP with the 45251SP 1:1, from that mixture; mix your paint, catalyst, 6396SP/45251SP combo as such, 3 parts paint, 1 part catalyst, 1 part 6396SP/45251SP reducer combo

\*Add in Sequential order based on percentages used in formulas.

Mix ratio = 3:1:1 (3=paint, 1=catalyst, 1= reducer)



# Matthews Paint Product Reference Guide: Conventional Satin

## Conventional Satin Intermix Colors 15-20° Gloss with Metallic Colors

N202SP White	N911SP Violet	N912SP Maroon	N913SP Magenta	N914SP Dark Red	N915SP Red Oxide	N917SP Yellow Oxide	N920SP Blue
N921SP Green	N923SP Black	N925SP New Blue	N929SP Carbon Black	N930SP Light Red	N931SP Trans Red Oxide	N932SP Trans Yellow Oxide	N940SP Red Yellow
N942SP Green Yellow	N947SP Scarlet Red	N951SP Medium Silver	N952SP Sparkle Silver	N953SP Super Sparkle Silver	N954SP Fine Silver		

Because of variations in monitors and printers, the colors shown above may vary from the actual toner colors.

### Catalyst Options:

- **43270SP** for spray application
- **43999SP** for spray applications requiring a slower dry time
- **43621SP** for brush or roll applications (Metallic paints are not recommended for brush or roll applications.)

### Reducer Options

- **6379SP** = Fast for cool weather applications not lower than 60-75°
- **45280SP** = Warm temp reducer for applications in temps between 70-80°
- **45290SP** = Hot weather applications with temps between 75-85°
- **6396SP** = Extreme Hot weather applications 85° and above
- **45251SP** = Retarder reducer must be used with 6396SP, to use this product; mix the 6396SP with the 45251SP 1:1, from that mixture; mix your paint, catalyst, 6396SP/45251SP combo as such, 3 parts paint, 1 part catalyst, 1 part 6396SP/45251SP reducer.

\*Add in Sequential order based on percentages used in formulas.

Mix ratio = 3:1:1 (3=paint, 1=catalyst, 1= reducer)