



Brush Cleaner

1S124

4004

A premium product designed for conditioning and cleaning brushes that have been used with oil based paints. Excellent for reconditioning, softening, and renewing partially hardened natural and nylon brushes and will not interfere with the properties of oil based sign paints.



Directions for Use:

- Clean brush thoroughly with 1 Shot 4004 Brush Cleaner.
- Rinse by stirring cleaned brush in second container of clean solution.
- Work a suitable brush oil into the brush's hair, making sure it works up into the ferrule.
- Partially hardened brushes can be softened in most cases by soaking for several days.
- Not intended for brushes that are completely hardened by paint or containing lacquer paint.

Technical Data:

VOC.....	5.98 lbs/gallon
Solids by Weight.....	14.89
Solids by Volume.....	12.17
Theoretical Coverage.....	195.16 square feet



Matthews Paint • Toll Free: 800.323.6593 • Fax: 800.947.0377
www.matthewspaint.com • www.1shot.com
760 Pittsburgh Drive • Delaware, OH 43015

Product Information Effective 01/17
Part No. 1S124 01/17
© 2017 Matthews Paint Company

Important:

This product contains Petroleum Distillates. See Warning and Caution statements on label.

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

Emergency Medical or Spill Control Information:

US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.